AC DC

WIFI CONTROL EASYADJUSTMENT

Solar Air Conditioner




Products Benefits

- Help you to reduce the 40%-80% electricity bill
- SEER up to 36 with solar, 22 without solar
- Enjoy cooling summer without grid in sunshine day
- Lower investment than off-grid&on-grid solar energy system
- ncrease the value of your home
- Reduce your carbon footprint

Wiring diagram



Model1. With Grid Power




1. Grid Power

During the night, the A/C unit take the power from the grid power and running with same principle of regular air conditioner, the SEER is over 22, it can saving 20-30% energy compare with the regular AC unit.

2. GRID AND SOLAR

When Sunshine is weak, like the evening or cloudy day, The A/C unit will take the solar as the priority choice, the insufficient power will take from the grid to make sure 24H working.



3. 100% Solar

When solar energy meet the Mic-Running requirement of compressor, the A/C unit can start and operate by solar energy only, even the grid off , 100% energy saving. In some time, the system will charge the battery automatically.

4. Grid Off

When the grid off or the customer turns off the grid power, the system will automatically take the battery energy to run the A/C unit, It will ensure you enjoy cooling summer in any situation.

Model2. Without Grid Power



1. Battery Power

During the night or the solar energy is weak, the A/C unit takes the power from the battery to run the A/C Unit.

2. Battery & Solar

When Sunshine is weak, The A/C unit will take the solar as the priority choice, the insufficient power will take from the Battery.

3.100% Solar

When solar is sufficient, the A/C unit can start and operate by solar energy only. In some time, the system will charge the battery automatically.

Free Cooling In The Summer

SOLAR AIR CONDITIONER





Cool air is easy to handle



In Heating Mode
Rapid Heating to 40C in 60"

In Cooling Mode
Rapid Cooling to 18C in 30"



- AC/DC auto-balance
- 97% saving in adaptime
- PV18ADC-driven

Model			HYBRID-AC9CE3	HYBRID-AC9CE18	HYBRID-AC9CE24
Capacity	Cooling	W	9000 (3000~12000)	18000 (6000~24000)	24000 (8000~30000)
	Heating	W	10000 (3000~12000)	19000 (6000~24000)	25000 (8000~30000)
Electric Data					
Power Input	Cooling	W	600	1200	1600
	Heating	W	500	1100	1500
Rated Current	Cooling	A	4.5	8.5	11.5
	Heating	A	4.5	8.5	11.5
Power Supply		Hz/Ph/V	50~60Hz, 1Ph, 220V/230V/240V	50~60Hz, 1Ph, 220V/230V/240V	50~60Hz, 1Ph, 220V/230V/240V
Performance					
EER	Cooling	W/W	4.5	4.26	4.75
	Heating	W/W	4.5	4.26	4.75
COP	Cooling	W/W	3.33	3.3	3.8
	Heating	W/W	3.33	3.3	3.8
APFw	Cooling	W/W	6.5	6.5	7.5
Noise	Indoor unit	dB(A)	35-47-51	36-46-56	36-46-56
	Outdoor unit	dB(A)	57	57	58
Dimension & Weight					
Dimension (L*W*H)	Indoor unit	MM	807*207*315	807*207*315	1039*303*397
	Outdoor unit	MM	780*320*540	780*320*540	1039*303*397
Net Weight	Indoor unit	KG	9KG/10KG	9KG/10KG	13KG/14KG
	Outdoor unit	KG	35KG/38KG	35KG/38KG	52KG/56KG
Gw Weight	Indoor unit	KG	10KG	10KG	14KG
	Outdoor unit	KG	37KG	37KG	54KG
Cooling Quantity	43?dry	W/h	230	230	720
Refrigerant					
Setup/Add Lefth		G	1800	1800	2800/ 60M
Refrigerant Type			R32	R32	R32
Application Area	Cooling	㎡	15-25	15-25	25-40
	Heating	㎡	15-25	15-25	25-40

Product list

Patent certificate